



TURNKEY®

Recommandations d'équipement entre le poids machine et sa force de cavage
Equipment recommendations between machine weight and its breakout force

(B.O.F= Break Out Force) expressed in Tons (T)

Taille / Size		T3		T4		T5		T7		T8		T9	
Machine		Standard	HD	Standard	HD	Standard	HD	Standard	HD	Standard	HD	Standard	HD
 Excavatrice Excavator	Poids Max. Max. Weight (T)	10.5T	8T	15.7T	12T	21.7T	16.3T	30T	22.5T	40T	30T	55T	40T
	Max. B.O.F 	8T	6.5T	11T	8.8T	15T	12T	19T	15.5T	25T	20T	32T	25.6T
 Chargeuse Wheel Loader	Poids Max. Max. Weight (T)	11.55T	8.9T	16.7T	12.9T	25T	19.5T	33.8T	25T	47T	33.5T	63.6T	46.9T
	Max. B.O.F 	11.5T	8.9T	16.7T	12.9T	25T	19.5T	32.6T	25T	39.9T	32.3T	49.2T	39.9T

1 Tonne = 9.8067 Kn

Préconisation valable pour un godet Standard d'excavatrice équipé de 5 dents ou de chargeuse équipé de 8 dents.
Recommendation valid for a Standard excavator bucket equiped with 5 teeth or equiped with 8 teeth for loader.

En cas d'usage extrêmement sévère, prendre une taille au-dessus.
In case of extremely severe use, oversize by one size.

Les applications et les conditions de travail doivent être prises en considération, veuillez consulter votre concessionnaire FEURST.
Applications & working conditions must be taken into consideration, please consult your FEURST dealer.

Données à titre de recommandations, en aucun cas la responsabilité de FEURST ne pourrait être engagée.
Data provided for recommendation purposes only, under no circumstances can FEURST's liability be engaged.

